Current MVDS Equipment

- PHILIPS Transmitter Unit specification
 - 4 transmitter units, each with 8+1 (redundant) transceiver
 - Redundant transmitter on Hot Standby (200 MHz bandwidth)
 - Seperate transmitter for each channel
 - PA technology MMIC GaAs pHEMT Power is 23 dBm per channel
 - cost approx £800 each in volume
 - By 1996 transmitter powers of 1 Watt per channel could be available
 - Horn Antenna for each channel => 15 dB gain
 - Cost estimate: £33,000-£57,000 for transmitter station

_GENERICS

Transmitter Unit #4 Transmitter Unit #1 Philips Transmitter Unit PA \ PA . A A Baseband Video Distributor

GENERICS


.


Current MVDS Equipment

- Receiver Unit
 - Based on commercially available satellite DTH Downconverter
 - Extra downconversion stage from 40 GHz to 12 GHz (1st IF)
 - 2nd IF: 950 2000 MHz
 - 2nd IF fed into standard satellite DTH receiver set-top box
 - Rx Antenna
 - Horn Antenna
 - Small size low cost
 - High Gain (32 dBi) so eliminates need for LNA in Receiver
 - estimated cost for 40 GHz MVDS receiver (excluding indoor set-top box) is £65 - £130

_GENERICS

Philips Receiver Unit





Current MVDS Equipment

- Other Hardware Providers
 - GEC Marconi, UK
 - Working on 40 GHz MVDS demo, available June 1995
 - On target for production late 1995
 - 40 GHz components available from a number of suppliers:
 - Farran Technology, Ireland
 - Thompson CSF
 - RACAL

SUMMARY

- Philips are developing 40 GHz equipment which will be available in production by August 1995
- Eurobell intend to use Philips equipment in their local delivery franchise which will begin in 1996
- Digital MVDS is currently being devloped which can provide approx 300 channels in 1 GHz
 - Philips plan to have this 40 GHz digital equipment in production by end of 1996

April 1995

SPACEWAYTM

Providing Affordable Telecommunications

HUGHES

Hughes Is a Global Wireless Telecommunications Provider

HUGHES



- Satellites
- Digital cellular equipment
- VSAT networks



Services

- Satellite system operator
- Leasing for government applications
- Business systems integrator
- Direct-to-home television entertainment
- Mobile satellite service provider



h C'GHE

Telecompunication and Space Segmen



Technologies

45 countries

Markets

• Telecommunications

equipment in use in

- Digital direct broadcast television
- Space-based digital processing
- ETDMA
- Fixed Wireless
- Local area networks and <u>internetwo</u>rking

Hughes is a world leader in many of the products and services we provide.


SPACEWAYTM Overview




- Provides worldwide "bandwidth on demand"
 - Interactive, digital, low cost, Ka-band communications services: voice, data, images and video
- Communication at rates from 16Kbps to 1544 Kbps and higher and compatible with terrestrial services
 - Multiple Satellite constellation serving four interconnected regions:

North America, Asia Pacific, Central/South America, and Europe/Africa

- Service initiates 1998: global coverage in place by 2000
- Low cost (<\$1,000), easily installable Ultra Small Aperture Terminals (26") accessible to mass markets
- Supports over 5 to 10 million subscribers





SPACEWAYTM IS A UNIQUE SATELLITE SYSTEM



19 APRIL 1995

MARKET BENEFIT

SPACEWAYTM ARCHITECTURE

- AFFORDABLE SERVICE
 - LOW COST

- PAY FOR WHAT YOU USE
- WIDE RANGE OF APPLICATIONS
 - TELEPHONY
 - POINT OF SALE
 - VIDEO CONFERENCING
 - REGIONAL DTH
- FULL CONNECTIVITY
 - POINT-TO-POINT
 - LAN
 - MULTICAST / BROADCAST

- SPOT BEAM ARCHITECTURE
 - LARGE SYSTEM CAPACITY
 - TWELVEFOLD FREQUENCY REUSE
 - SMALL TERMINALS / NEXT GEN VSAT
- BANDWIDTH ON DEMAND


FAST PACKET SWITCHING

- WIDE RANGE OF DATA RATES
 - 16 KBPS TO 1.5 MBPS (20 MBPS)
 - CONSTANT BIT RATE / BURSTY SERVICES
 - 92 MBPS DOWN LINK
- ON BOARD ROUTING
 - SINGLE HOP BEAM-TO-BEAM
 - FULL MESH CONNECTIVITY
 - ATM COMPATIBLE

SPACEWAYTM

Spot Beam Technology Permits High Frequency Reuse and High System Capacity





SPACEWAYTM Enables a Wide Range of Applications 100 Mbps **PBX LAN Optional Broadband** 50 Mbps **Bulk transport** 25 Mbps **Uplink Terminal HDTV** 10 Mbps **Ethernet** Broadcast-quality video 6 Mbps 2 Mbps VCR-quality video 1544 kbps **Document imaging** Data access and distribution **HDR** bursty LAN internetworking 384 kbps High quality or multiplexed 144 kbps Video and videoconferencing/ISDN 64 kbps Desktop videoconferencing/ISDN 16 kbps Voice and voice-band data Iridium, LDR bursty Transaction processing/e-mail/VSAT services Globalstar 4.8 kbps Narrowband voice/data **Inmarsat P21** LDR - Low Data Rate Messaging/paging Odyssey 1.2 kbps HDR - High Data Rate LDR bursty **Transaction processing**

SPACEWAYTM

Performance Summary

HUGHES

Satellite

Type: HS601 Lifetime: 15 yrs

Dry weight: 3,785 lbs Eclipse capacity: 100% Bandwidth: 500 MHz

Number of communication beams: 48
Communication beam bandwidth: 125 MHz

BER performance: 1 x 10-10

Transmitter redundancy: 64 for 48

Modulation: QPSK

Data stream: FDM/TDMA Uplink

TDM Downlink

Data throughput: 4.6 Gbps
Downlink data rate: 92 Mbps

Downlink EIRP: 60 (dBw) Peak; 55 Edge Inter satellite links: 60 GHz; 1 Gbps

Capacity per satellite

Kbps	16	128	384	1,544	2,048
Simultaneous simplex channels	230,400	34,560	11,520	2,880	2,304

USAT

Size: 66 cm to 2 m

Uplink power: 0.1w to 2.0 w

Standard Terminal:

Uplink data rates: 16 kbkps to 1.544 Mbps Downlink data rates: 16 kbps to 92 Mbps

Optional Uplink Terminal:

Uplink data rates: Up to 6 Mbps



SPACEWAYTM Services are Market-Focused



Infrastructure Enhancment		<u>Interactive Multimedia</u>			
• Rapid build-out —	- Available 1998	Rapid deployment — -	<u> </u>		
-	Digital transmission		"One stop shop"		
	quality	 Bandwidth-on- demand 	 Versatile service offerings; usage based pricing 		
	 Significantly superior to mobile alternatives 				
		High data rates	 Up to E1 (2.048 Mbit/sec) 20 Mbps with optional 		
	- Echo cancellation		uplink terminal		
• Ease-of-use	 16 Kbps toll quality voice 	Compatible with	- ATM		
	Seamless terrestrial interconnectivity	latest terrestrial	- Frame Relay		
	 Local, long distance, 		- ISDN		
	international connections	-	- Videoconferencing		
• Lower cost	High system capacity	• High quality	- Greater than 99.5%		
	 Regional implementation 		availability		
	 Mass produced USATs 	-	 BER comparable with terrestrial ATM (fiber) 		
	 Service charges competitive with terrestrial wireline 	• Lower cost	- Lower priced equipment and service than terrestrial alternatives		

SPACEWAYTM flexibility allows the system to evolve as markets develop, shifting seamlessly between voice and wideband telecommunications.

SPACEWAY™ Provides High Quality Telephony Service

HUGHES

Cost Effective

Competitive with terrestrial alternatives in many areas.

Affordable service to underserved.

Modest Delay

Single hop delay less than 320 ms

No Echo

All digital technology incorporates echo cancellation

High Quality

16 Kbps ensures much better voice quality than mobile alternatives


Affordable, High Capacity

SPACEWAY™ system capacity ensures more affordable prices than mobile alternatives




...Fulfilling the Needs of the Underserved

Telephony Services



- 90% of the 600,000 villages in India have no form of telephone service.
- "To better serve their 1.2 billion population and exponential economic growth, they [China] are annually adding approximately 10 million new main lines, 500,000 new mobile subscribers, 5 million new paging subscribers...."
 - -Telecommunications Industry Association

Wideband Services



INCREASED TRANSMISSION RATE SPACEWAYTM OFFERS HIGH DATA RATES



19 APRIL 1995

DOCUMENT	INFORMATION	PHONE LINE	SPACEWAY TM	SPACEWAY TM
		(9.6 kbps)	(384 kbps)	(1.5 Mbps)
РНОТО	1 MBIT	1.7 MIN	2.6 SEC	0.7 SEC
CAD/CAM	2 MBITS	3.4 MIN	5.2 SEC	1.4 SEC
CT SCAN	5.2 MBITS	9.0 MIN	13.5 SEC	3.4 SEC
X RAY	12 MBITS	21.0 MIN	31.3 SEC	7.8 SEC


SPACEWAY™ High Capacity for Each Region

HUGHES


Each satellite provides:

- Reliable service throughout region
- Basic telephony/fax and wideband data for multimedia applications
- 6 GHz effective bandwidth per satellite using polarization and spatial reuse

North America




Central & South America



Asia-Pacific



Europe & Africa



SPACEWAYTM CAPACITY SUMMARY SIMULTANEOUS SIMPLEX CIRCUITS



19 APRIL 1995

	16 kbps	<u>128 kbps</u>	<u>384 kbps</u>	<u>1544 kbps</u>
SINGLE FOOTPRINT	9,600	1,440	480	120
ONE SATELLITE	230,400	34,560	11,520	2,880
REGIONAL SYSTEM (4 SATELLITES)	921,600	138,240	46,080	11,520
WORLD WIDE SYSTEM (17 SATELLITES)	3,916,800	587,520	195,840	48,960

ROBUST MARKETS



PRIMARY APPLICATIONS:

- INFRASTRUCTURE ENHANCEMENT
 - **TELEPHONY**
 - FAX / DATA
 - TRANSACTION PROCESSING (VSAT SERVICES)
- INTERACTIVE MULTIMEDIA
 - HIGH SPEED DATA TRANSFER (LAN INTER-NETWORKING)
 - VIDEO CONFERENCING (DESKTOP & GROUP)
 - DISTANCE LEARNING
 - TELE-IMAGING / TELEMEDICINE
 - **TELECOMMUTING**

SECONDARY APPLICATIONS

- BROADCAST QUALITY VIDEO (REGIONAL DTH, HDTV)
- HIGH SPEED DATA DISTRIBUTION (VIDEO)
- MULTICASTING / DATA CASTING
- IMMEDIATE INFRASTRUCTURE (EMERGENCY / RAPID DEPLOYMENT)

Markets and Applications

045 Retall/Franchise Telecommuters Contractors Contractors Professional Services Healthcare

Markets and Applications (Continued)

OF 9/8/ Ouls se oot de louis estrett Outreut, alay **Luxury Homes** Manufacturing Agriculture Banks